

SEE NOTE #2

SEE NOTE #4

SEE NOTE #2

SWITCHING SCHEMATIC FOR GYM
EMERG. LTG.
CIRCUITS E2-234

NOTE: FOR CHORUS ROOM FIXTURES
USE VOIGHT CO. CAT # 711 SHADE
WITH PERFORATIONS AND NO GUARDS.
MOUNT 18" FROM FLOOR.

NOTE: ALL FIXTURES IN THIS ROOM TO BE
MOUNTED ON 14" STEMS FROM BOTTOM OF
BAR JOISTS. FIXTURE SIGN TO CORRESPOND
TO THAT OF THE BAR JOISTS 18" SWAYEL HANGERS
ARE REQUIRED.

- NOTES:
1. ALL WIRING SHOWN ON THIS SHEET TO BE #10 UNLESS NOTED OTHERWISE.
 2. ALL FIXTURES IN THIS ROOM TO BE MOUNTED 10" FROM FLOOR TO BOTTOM OF FIXTURE 15" SPACEL.
 3. ALL FIXTURES ARE 200 W. WITH GUARDS MOUNTING HT. 18" IT.
 4. ALL CONDUITS TO REMAIN AND THE NEW EMERGENCY LIGHTING CONDUIT TO 40 DOW THEN OUTSIDE WALL IN THE AREA, ALSO PROVIDE SPARE CONDUITS FOR FUTURE USE OF THE SPARE BREAKERS IN PANEL 'D'.

GYMNASIUM - THIRD FLOOR PLAN
SCALE 1/8" = 1'-0"

DATE NOV. 10, 1953	THIRD FLOOR PLAN - GYMNASIUM	SH. E-5
CERTIFIED BY	PHYSICAL EDUCATIONAL BUILDING	
	VICTOR L. HAWKINS HIGH SCHOOL	
	CHICAGO, ILL.	
	SCHUYT-HALEY, ASSOCIATES	
	ARCHITECTS AND ENGINEERS	
	510 JEFFERSON ST.	GARY, IND.