

REMOVE SOUTHWEST CORNER BEFORE SEALING

EXISTING INSTRUCTIONAL MATERIAL CENTER

PLAN NOTE #1

90'±

20'

23'5'±

51'6"

5TH STREET

PLAN NOTE #6

63'


23'±

40'±

3/1

3/3

3/6



SECTION
NO SCALE

SEE PLAN

1" BITUMINOUS SURFACE COURSE

2" BITUMINOUS BINDER COURSE

REMOVE EXISTING BINDER AND SURFACE.

EXISTING BITUMINOUS PAVEMENT

2" #55 CRUSHED STONE

EXISTING BASE

4" #2 & 4 CRUSHED STONE

RECOMPACT SUBGRADE

	EXISTING BITUMINOUS PAVING WITH NEW SEAL COAT
	EXISTING BITUMINOUS PAVING WITH NEW SURFACE COURSE
	NEW BITUMINOUS PAVING
	EXISTING BITUMINOUS PAVING TO BE REMOVED AND REPLACED
	EXISTING CHAIN LINK FENCE
	EXISTING WOOD FENCE
	DRAINAGE VALLEY

1. REMOVE EXISTING PAVEMENT & BASE.
2. REMOVE EXISTING SPEED BUMP-PATCH PAVING.
3. OMIT TOPPING AT POLE ENCLOSURE.
4. NEW PAVING TO EXTEND TO EXISTING FENCE
5. REMOVE ALL LOOSE GRAVEL
6. TAPER TOPPING TO MEET EXISTING PAVING.

