

NOTES:

1) INSULATION SHOWN ON THIS DRAWING IS FOAMULAR BY OWENS CORNING, INSULATION IS EXTRUDED POLYSTYRENE.

2) LAY TAPERED BOARDS BY LETTER AS INDICATED. THE NUMBERS FOLLOWING EACH LETTER REFER TO THICKNESS OF FILL BOARDS AS PER CROSS SECTION VIEW.

3) ALL HIPS, VALLEYS AND CRICKETS ARE TO BE FIELD CUT. MATERIAL WILL BE SUPPLIED.

4) ROOF DIMENSIONS USED TO DRAW THIS PLAN WERE FROM ARCHITECTS PLANS SUBMITTED, THE ROOFING CONTRACTOR SHOULD CHECK DIMENSIONS BEFORE MATERIAL HAS BEEN MANUFACTURED AND CONTACT OWENS CORNING TAPER CONTROL CENTER OF ANY CHANGES. ANY ALTERATIONS AFTER PRODUCTION OF MATERIAL MAY RESULT IN ADJUSTMENT OF ORIGINAL PRICE.

5) APPROVED SIGNED SHOP DRAWINGS MUST BE RETURNED TO OWENS CORNING TAPER CONTROL CENTER PRIOR TO RELEASE OF MATERIAL FOR FABRICATION.

6) MANUFACTURER IS NOT RESPONSIBLE FOR SAFEKEEPING NOR MATERIAL SHORTAGES AFTER SIGNING FOR RECEIPT OF OWENS CORNING MATERIAL.
7) IT IS REQUIRED THAT THE ROOFING MEMBRANE AND INSULATION

BE BALLASTED IMMEDIATELY AFTER PLACEMENT. FOR MORE DETAILS PLEASE REFER TO CURRENT FOAMULAR LITERATURE OR CONTACT YOUR LOCAL OWENS CORNING SALES REPRESENTATIVE.

SECTION TAPERED PANELS:

RESULT IN ADJUSTMENT OF ORIGINAL PRICE.

0.50 - 1.00

1.00 - 1.50 SECTION FILL PANELS:

0.50

1.00

CRICKET TAPERED PANELS:

0.50 - 1.25 R 1.25 - 2.00

CRICKET FILL PANELS: 1.00



Project: CHESTERTON H.S. SWIMMING POOL CHESTERTON, INDIANA

Architect:FANNING & HOWEY

Material: THERMAPINK 25

Roofer: KELSO ROOFING

KEY PLAN

Scale: 1/16" = 1'00"Drawn: T.L.I. Slope: VARIES Checked: R.E.G. Date: 6/11/98 T-21897F

Drawing number: 7 of 7

REVISIONS

- REVISED DRAWING FOR RELOCATION
- OF ROOF DRAINS PER W. R. KELSO. 2. CHANGED TAPER LAYOUT, SADDLE SLOPE AND THICKNESS PER FANNING & HOWEY 2/6/98
 3. CHANGE SLOPE TO 1/4" 4/14/98
- CHANGED SLOPES IN VARIOUS ROOF AREAS AN MOVED DRAINS. 5/14/98
 CHANGED DIRECTION OF SLOPE TO MAINTAIN 3 MAX DISTANCE BETWEEN DRAINS. 6/11/98